

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number  
**WO 2005/009541 A1**

(51) International Patent Classification<sup>7</sup>: **A62B 1/06**

(21) International Application Number:  
PCT/KR2004/001785

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2003-0051573 25 July 2003 (25.07.2003) KR

(71) Applicant and

(72) Inventor: CHUN, Jung-Myung [KR/KR]; 12-2, Young-  
woon-ri, Sanyang-up, Tongyeong city, Kyongsannam-do  
650-943 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIM, Myoung-Oh

[KR/KR]; Room. 502, Samsung Apt 2dong, 290-2, Man-  
duk-dong, Puk-gu, Pusan 616-826 (KR). CHUN, Jae-Ry-  
oong [KR/KR]; Room.B-9, 1398, Chongnyang-dong,  
Tongyeong city, Kyongsannam-do 650-030 (KR).


(74) Agent: CHUN, Hoy-Nam; Room No. 206, Hanju Bldg  
647, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: PERSONAL DESCENT APPARATUS



(57) Abstract: A personal descent apparatus for evacuating occu-  
pants from a high elevation of tall building under emergency. The  
personal descent apparatus comprises a pair of supporting plates  
connected to each other front and rear with a predetermined gap,  
braking rods rotatably fixed to the pair of supporting plates in the  
predetermined gap between the pair of supporting plates, the brak-  
ing rods form a passage which is formed by two guide grooves each  
of which is tapered and formed at arc ends facing to each other, so  
that a rope is inserted to the passage, and weight receiving means  
connected to both ends of the braking rods for receiving a load,  
wherein the braking rods are rotated by the load.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report